

B-10063

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 9/21/2018

1. PRODUCT & COMPANY IDENTIFICATION						
1.1	Product Name:	#mydentity MyDirtySide Dry Shampoo				
1.2	Chemical Name:	Aerosol Powder Spray				
1.3	Synonyms:	mydentity Dry Shampoo – B-10063				
1.4	Trade Names:	mydentity MyBody Armour Dry Shampoo				
1.5	Product Uses/ Restrictions	Professional and Cosmetic Use				
1.6	Distributor's Name:	KIK Custom Products				
1.7	Distributor's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA				
1.8	Emergency Phone:	CHEMTEL: +1 (703) 527-3887 / +1 (800) 424-9300				
1.9	Business Phone / Fax:	+1 (770) 534-0300 / +1 (770) 534-8954				

#### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)

DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.

<u>Classification:</u> Level 3 Aerosol; Category 1 Extremely Flammable Aerosol

<u>Hazard Statements</u> (H): H-222– Extremely Flammable Aerosol. H229–Pressurized container: may burst if heated. H320 – Causes eye irritation.

<u>Precautionary Statement</u> (P):

P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

P211 – Do not spray on an open flame or other ignition source.

P251 – Do not pierce or burn, even after use.

P261 – avoid breathing vapors/spray.

P271 – Use only in well-ventilated area.

P304+P340 – IF INHALED; Remove person to fresh air and keep comfortable for breathing.

P305+P351+338 – IF INEYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present, continue rinsing.

P337+P313 – If eye irritation persists: Get medical advice/attention.

P410+P412 – Protect from sunlight. Do no expose to temperature exceeding 48°C (120 °F).

P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.



### 3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
Propane	74-98-6	200-827-9	8 - 20	Flam. Gas 1; H220
Isobutane	75-28-5	200-857-2	40 – 60	Flam. Gas 1; H220
Ethanol (SD Alcohol 40B)	64-17-5	200-578-6	20 - 40	Flam. Liq. 2; H225

#### 4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		Eyes:	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
		Eyes:	Moderately irritating to the eyes.



B-10063

	Prepared to OSHA, ACC, ANS	SI, NOHSC, WH	MIS, 2001/58 & 1272/2008/EC Standards SDS Re	evision: 1.0 SD	S Revision Date:	9/21/2018	
		Inhalation:	Vapors of this product may be moderately irritating to respiratory system. Symptoms of overexposure can in difficulty breathing. Inhalation of concentrated vapors drowsiness, dizziness, headaches, nausea).	nclude coughing, s can cause nervo	wheezing, nasal ous system depre	congestion, and	
4.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and cent	ral nervous syste	m depression.		
		Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas.					
		Eyes:	Overexposure in eyes, may cause redness, itching and may cause mild eye irritation including stinging, water	ing and redness.			
		<u>Inhalation:</u> Symptoms of overexposure can include coughing, wheezing, nasal congestion, and					
4.4	Acute Health Effects:	drowsiness,	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.				
4.5	Chronic Health Effects:	irritating to s	or chronic health effects are expected to occur from a sir kin and mucous membrane of the eye and respiratory sy some sensitive individuals. May also induce skin sensiti atitis.	ystem. Overexpo	sure may trigge	asthma-like	
4.6	Target Organs:	Eyes, skin, re	spiratory system.				
4.7	Medical Conditions		hazards may be delayed. Most common symptoms	HEALTH		1	
	Aggravated by Exposure		ting properties to eyes, respiratory system and skin.	FLAMMABILITY		3	
		_	natological conditions (such as eczema) and respiratory	PHYSICAL HAZARDS		0	
			uch as bronchial asthma and/or bronchitis) may be	PROTECTIVE EQUIPMENT		В	
		exacerbated.		EYES	SK IN		
			5. FIREFIGHTING MEASURES				
5.1	Fire and Explosion Hazards:	Level 3 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120° F (48°C). Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids and/or exposed gases if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished.					
5.2	Extinguishing Methods:	Water Fog, Foam, CO <sub>2</sub> , Dry Chemical					
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand_ and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personnel. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.					
	<u>I</u>						
	1		6. ACCIDENTIAL RELEASE MEASUR	RES	<b>'</b>		
6.1	Spills:	Equipment (I Small spills W combustible not use wate (e.g., plastic I Large spills: It release. Isola	6. ACCIDENTIAL RELEASE MEASUR ing any spill or leak, individuals involved in spill cleanup (PPE).  Vear appropriate personal protective equipment includir material such as vermiculite or sand to soak up the product or or a material such as "speedy dry" to soak up material brooms, shovels, dustpans) and place into a plastic contact (seep incompatible materials (e.g., organics such as oil) are the immediate hazard area and keep unauthorized personinimal risk. Wear appropriate protective equipment inclinations.	must wear appro ng gloves and pro duct and place int . Sweep up mate ainer or plastic lin way from spill. S onnel out of area	otective eyewear to a container for erial using non-sp ner within anoth tay upwind and a . Stop spill or rel	. Use a non- r later disposal. D parking materials er container. away from spill or ease if it can be	
6.1	Spills:	Equipment (I Small spills W combustible not use wate (e.g., plastic Large spills: k release. Isoladone with mi	ing any spill or leak, individuals involved in spill cleanup (PPE).  Vear appropriate personal protective equipment includir material such as vermiculite or sand to soak up the produce or or a material such as "speedy dry" to soak up material brooms, shovels, dustpans) and place into a plastic contacted incompatible materials (e.g., organics such as oil) are timmediate hazard area and keep unauthorized personal.	must wear approng gloves and product and place into Sweep up materials are or plastic ling way from spill. Sonnel out of area luding respirator	otective eyewear to a container for erial using non-sp ner within anoth tay upwind and a . Stop spill or rel y protection as co	. Use a non- r later disposal. D parking materials er container. away from spill or ease if it can be onditions warrant	



B-10063

.1 E P C C C .3 R	Exposure Limits: Ppm (mg/m³)  Ventilation & Engineering Controls Respiratory Protection:	handling. In instances where d protection is needed, use only State regulations, or the Canad	ACC TLV 1000 1000 600 or naturally remove	S & P GIH STEL 3000 NA 750 al ventilae and pr	ES-TWA 1000 1000 NF		-	PEL 1000	OSHA STEL 1900	IDLH 3300	OTHER				
3.2 V C C S.3 R	Ppm (mg/m³)  /entilation & Engineering Controls  Respiratory Protection:	Chemical Name(s)  Ethanol (SD Alcohol 40B)  Propane Isobutane  General mechanical (e.g., fans) exhaust ventilation to effective product.  No special respiratory protection handling. In instances where disprotection is needed, use only State regulations, or the Canadians.	TLV 1000 1000 600 or naturally remove	STEL 3000 NA 750 al ventila e and pr	ES-TWA 1000 1000 NF	NOHSC ES-STEL 1800	ES-PEAK NF	PEL 1000	STEL		OTHER				
P 23.2 V C C 23.3 R 23.4 E	Ppm (mg/m³)  /entilation & Engineering Controls  Respiratory Protection:	Ethanol (SD Alcohol 40B)  Propane Isobutane General mechanical (e.g., fans) exhaust ventilation to effective product.  No special respiratory protection handling. In instances where disprotection is needed, use only State regulations, or the Canada	TLV 1000 1000 600 or naturally remove	STEL 3000 NA 750 al ventila e and pr	1000 1000 NF	ES-STEL 1800	NF	1000	STEL		OTHER				
8.2 V C C	/entilation & Engineering Controls Respiratory Protection:	Ethanol (SD Alcohol 40B)  Propane Isobutane General mechanical (e.g., fans) exhaust ventilation to effective product.  No special respiratory protection handling. In instances where disprotection is needed, use only State regulations, or the Canada	1000 1000 600 or naturally remove	3000 NA 750 al ventila e and pr	1000 1000 NF	1800	NF	1000							
8.3 R	Controls Respiratory Protection:	Propane Isobutane General mechanical (e.g., fans) exhaust ventilation to effective product. No special respiratory protection handling. In instances where disprotection is needed, use only State regulations, or the Canad	1000 600 or natura ly remove	NA 750 al ventila e and pr	1000 NF				1900	3300					
C R R R R R R R R R R R R R R R R R R R	Controls Respiratory Protection:	Isobutane  General mechanical (e.g., fans) exhaust ventilation to effective product.  No special respiratory protection handling. In instances where d protection is needed, use only State regulations, or the Canad	600 or natura ly remove on is requ	750 al ventila e and pr	NF	NF	NF								
C R R R R R R R R R R R R R R R R R R R	Controls Respiratory Protection:	General mechanical (e.g., fans) exhaust ventilation to effective product.  No special respiratory protection handling. In instances where disprotection is needed, use only State regulations, or the Canad	or natura ly remove	al ventila e and pr				1000	NA	2100					
C R R R R R R R R R R R R R R R R R R R	Controls Respiratory Protection:	exhaust ventilation to effective product.  No special respiratory protection handling. In instances where disprotection is needed, use only State regulations, or the Canad	ly remove on is requ	e and pr		NF	NA	NA	NA	NA					
3.4 E		No special respiratory protection handling. In instances where d protection is needed, use only State regulations, or the Canad													
3.4 E		handling. In instances where d protection is needed, use only State regulations, or the Canad													
	Eye Protection:	protection is needed, use only State regulations, or the Canad	usts of th	No special respiratory protection is required under typical circumstances of use or											
	Eye Protection:	State regulations, or the Canad	handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S.												
	Eye Protection:	_							S.						
	ye Protection:					and applica	ible standar	ds of							
	eye Protection.	Canadian Provinces, EC members  None required under normal co				contact S	afaty alacce	s should		_					
8.5 H		be used when handling or using							'	<b>E</b>	<b>2</b> 5				
	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation is some sensitive individuals. When handling large quantities (e.g., $\geq 1$ gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.													
8.6 B	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs.), eye wash station and deluge showers should be available. Upon completion of													
work activities involving large quantities of this product, wash any exposed areas															
		thoroughly with soap and wate	r.												
		0 DHACICY	1 9. CL		CAL DD	ODEDT	TEC								
0 1 1 4	Annoaranco:		9. PHYSICAL & CHEMICAL PROPERTIES  erosol, misty powder spray												
	Appearance: Odor:		esh Sweet odor												
	Odor Threshold	NA													
	oH:														
	Melting/Freezing Point	NA	NA NA												
	nitial Boiling Point/ Boiling														
	Range:														
	Flashpoint:	-30 °F (-34 °C) TCC for propellant only; 35.6 °F (2 °C) EPA method 1010 Concentrate only													
	Jpper/Lower Flammability imits	NA													
	/apor Pressure:	@ 20 °C (68° F) – Can pressure	not to ex	ceed 180	) psig @ 5	5 °C (131 °F	12.4 bar								
	/apor Density	>1		3	, , , ,	,	,								
	Relative Density:	0.85 - 0.95													
9.12 S	Solubility:	Soluble													
	Partition Coefficient log Pow):	NA													
	Autoignition Temperature:	NA													
	Decomposition	NA													
	Temperature.														
		Aerosol at ambient temperatur	e												
9.16 V	/ISCUSILY.	Evaporation Rate >1													



B-10063

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 9/21/2018

		10. STABILITY & REACTIVITY
10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO <sub>2</sub> ) and sulfur (SO <sub>2</sub> )
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.
10.5	Incompatible Substances	Mixture with strong acids, alkalis or oxidizers.
		11. TOXICOLOGICAL INFORMATION
11.1		Inhalation: YES Absorption: YES Ingestion: YES
11.2	Toxicity Data:	This product was not tested on animals.
11.3	· · · · · · · · · · · · · · · · · · ·	See Section 4.4
11.4	· · · · · · · · · · · · · · · · · · ·	See Section 4.5
	Suspected Carcinogen:	NA NA
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.
	Irritancy of Product:	See Section 4.3
11.8	Biological Exposure Indices:	NA NA
11.9	Physician Recommendations:	Treat symptomatically.
		12. ECOLOGICAL INFORMATION
12.1	Environmental Stability:	There is no specific data available for this product.
12.2		There is no specific data available for this product.
12 3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.
12.3	Effects off Aquatic Life.	The product tisen has not been tested as a whole. There is no specific data available for this product.
		13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)
		14. TRANSPORTATION INFORMATION
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or
		CONSUMER COMMODITY, ORM-D (IP VOL $\leq$ 1.0 L) – until 12/31/2020
14.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or
	, ,	ID8000, CONSUMER COMMODITY, ORM-D (IP VOL < 0.5 I=L)
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)
14.4		UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or
	· .	MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)
	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL < 1.0 L)
	ADGR (AUS):	



B-10063

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 9/21/2018

		15. REGULATORY INFOR	MATION	
15.1	SARA Reporting Requirements:	This product does not contain any substance subject to S	SATA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for t	he components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Ir	nventory.	
	CERCLA Reportable Quantity (RQ):	There are no specific Reportable Quantity	,	
15.5		This product complies with the appropriate sections of the (Cosmetics)	he Food and Drug Administration's 21 CFR Subchapter G.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List. WHMIS Class B5 (Flammable Aerosol)		
15.7	State Regulatory Information:	Ethanol: is found on the following state criteria lists FL, MA, MN, NJ, PA, and WA  Isobutane can be found on the following state criteria lists: MA, NJ, and PA.  Propane is found on the following state criteria lists: MA, MN, NJ, PA and WA  No other ingredients of this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substance List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Righto-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).		
15.8	Other Requirements:	The primary components of this product are listed in Anr Isobutane: Flammable (F+). Risk Phrases (R): 12 — Highl out of reach of children. Keep container in a well-ventil No smoking.  Propane: Flammable (F+). Risk Phrases (R). 12 — Highly F of reach of children. Keep container in a well-ventilated smoking, Flammable (F+)  Ethanol: Flammable (F). Risk Phrases (R): 11 — Flammabl children. Keep container tightly closed. Keep away from the story of the product of the pro	y Flammable. Safety Phrases (S): 2-9-16 – Keep lated place. Keep away from sources of ignition – lammable. Safety Phrases (S): 2-9-16 – Keep out place. Keep away from sources of ignition – No  e. Safety Phrase (S): 2-7-16 – Keep out of reach of	
		16. OTHER INFORMA	TION	
16.1	Other Information:	PANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSUR FLAMMABLE LIQUID AND VAPORS. CAUSES EYE IRRITA' and other ignition sources. No Smoking. Do not spray or even after use. Avoid breathing vapor/spray. Wash thor ventilated area. Wear eye protection. Protect from sunl INHALED: Remove person to fresh air and keep comforts.	RIZED CONTAINER: MAY BURST IF HEATED, HIGHLY TION. Keep away from heat, hot surfaces, sparks open flames in an open flame or other ignition source. Do not pierce or burn, roughly with soap and water after handling. Use only in a well light. Do not expose to temperature exceeding 48°C (120°F). IF able for breathing. IF IN EYES: Rinse cautiously with water for easy to do. Continue rinsing. If eye irritation persists: Get	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.		
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or complete=ness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.		
16.4	Prepared By:	KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA http://www.kikcorp.com	KIK CUSTOM PRODUCTS	



B-10063

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 9/21/2018

Flammable	Explosive	Oxidizer
Pressurized	Corrosive	Toxic
Harmful/Irritating	Health Hazard	Environment
FFF .		
Face Shield and Protective Eyewear	Apron	Dust Mask
Scuba	Protective Clothing	Full Suit
Boots	Safety Glasses	Gloves



B-10063

SDS Revision Date: 9/21/2018

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

×

SDS Revision: 1.0

Irritant / Harmful



Biohazard



Oxidizing



Flammable



Infectious



Corrosive



Compressed



Toxic

(T)

Irritation